

# ULTRADECK

MARINE FLOORING

## CLEANING, CARE & WARRANTY

Your guide to effortless cleaning made simple!



# ULTRADECK

## MARINE FLOORING

### CLEANING, CARE & WARRANTY

#### Easy Cleaning:

We know you put your boat through a lot, which is why UltraDeck is designed and tested to be easily cleaned, durable, UV resistant, and anti-fatigue.

The product is very stain resistant, food, beverages, dirt, and fishing messes all clean out of UltraDeck® if they are handled properly and in a timely manner.



#### Cleaning Instructions:

- Rinse the surface to clear away any debris and ensure it is damp.
- Mist the Simple Green HD cleaner onto the UltraDeck surface, ensuring even coverage.
- Allow the cleaner to soak on the surface for a few minutes to loosen dirt and grime.
- Take a medium to firm deck brush and gently scrub the UltraDeck surface, following the grain of the material.
- Rinse the deck thoroughly with clean water to remove all traces of cleaner and dirt residue.

#### Product List (available at most hardware stores):

- Simple Green Pro HD
- ZEP Purple or comparable general de-greaser
- Bar Keepers Friend, Soft Cleanser - used as a last resort, extreme stains that nothing else will remove.

\*Do not use a pressure washer in close contact. Do not use acid-based cleaners or solvents with UltraDeck® as it will damage the product.

# ULTRADECK

## MARINE FLOORING

### Dealing With An Air Bubble:

While it's unusual for air pockets to form under your UltraDeck pads, under certain circumstances, it can happen. We recommend that customers carefully inspect their product after installation to prevent any air bubbles from forming due to expansion. These areas can enlarge over time due to temperature changes. It's important to address any concerns promptly to prevent potential issues down the line.

1. Apply firm pressure to push trapped air toward the nearest pattern line or edge by sliding your hand firmly.
2. With a large needle, carefully insert the tip through the bottom edge of the pattern line until you reach the substrate.
3. Gently press down on both sides of the incision to release trapped air beneath the pads.
4. Once done, the incision should naturally reseal itself as our adhesive is always active.

### Warranty:

UltraDeck® stands behind its quality with a comprehensive 5-year warranty, safeguarding against premature product breakdown. This warranty offers peace of mind to our customers, ensuring they can enjoy their UltraDeck® with confidence.

However, it's important to note that certain exceptions apply to this warranty coverage. Specifically, damage resulting from physical abuse, exposure to solvents, oils, or fuel, and staining are not covered. Additionally, instances of incorrect installation leading to adhesive issues fall outside the scope of warranty protection.

While our products are designed to withstand various environmental conditions and usage scenarios, adherence to proper installation guidelines and responsible maintenance practices is essential to maximize longevity and performance.

In summary, while UltraDeck® offers a robust warranty package, it's imperative for users to exercise care and diligence in handling, installation, and maintenance to uphold the integrity of their investment over time.